

### GENERAL INFORMATION

Category: Sterile sampling bags

Family: Twirl'em

Lifespan: 5 years

#### **TECHNICAL DESCRIPTION**

Twirl'em bags have a practical and easy-to-use closing system. They are made of a flexible, strong and transparent plastic.



## SPECIFIC INFORMATION

### ITEM

ITEMBagMaterial :Polyethylene blendColor :TransparentDimension :114 x 190 mm / 4.5 X 7.5 poThickness :2.5 mil.in/ 63.5 micron / 0.0635 mmTotal volume :490 ml / 17 ozFunctional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :YesEnd of product life :Recyclable		
Color :TransparentDimension :114 x 190 mm / 4.5 X 7.5 poThickness :2.5 mil.in/ 63.5 micron / 0.0635 mmTotal volume :490 ml / 17 ozFunctional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	ITEM	Bag
Dimension :114 x 190 mm / 4.5 X 7.5 poThickness :2.5 mil.in/ 63.5 micron / 0.0635 mmTotal volume :490 ml / 17 ozFunctional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Material :	Polyethylene blend
Thickness :2.5 mil.in/ 63.5 micron / 0.0635 mmTotal volume :490 ml / 17 ozFunctional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Color :	Transparent
Total volume :490 ml / 17 ozFunctional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Dimension :	114 x 190 mm / 4.5 X 7.5 po
Functional volume :290 ml / 9 ozPrinting type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Thickness :	2.5 mil.in/ 63.5 micron / 0.0635 mm
Printing type :ClearOpening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Total volume :	490 ml / 17 oz
Opening system :Perforated lineClosing system :Attachment with 2 round wiresSterile :Yes	Functional volume :	290 ml / 9 oz
Closing system : Attachment with 2 round wires   Sterile : Yes	Printing type :	Clear
Sterile : Yes	Opening system :	Perforated line
	Closing system :	Attachment with 2 round wires
End of product life : Recyclable	Sterile :	Yes
	End of product life :	Recyclable

## PACKAGING INFORMATION

Outer box dimension : (W x D x H)	16.38 po x 9.63 po x 9.63 po 42 cm x 24 cm x 24 cm
Box weight:	8.00 LB / 3.63 KG
Conditioning:	1000 (2 x 500)
Storage condition:	Store in a dry place at room temperature

### OTHER



# **EPL-4575**

# AVAILABLE DOCUMENTS

Data Sheet	Certificate of Compliance
Certificate of Analysis	Safety Data Sheet (SDS)
Certificate of Sterility	Pyrogen Declaration
DNase/RNase	

Reach out to us for additional resources, if applicable to this product.

DECLARATION	
CFIA	LABPLAS sampling bags are a solution that may be used in the CFIA Preventive Control Plan (PCP) for the seven principles of the HACCP system. The PCP is a Canadian federal initiative, under the Safe Food for Canadians Regulations (SFCR).
EU	The materials used to manufacture LABPLAS sampling bags meet, where applicable, the Eu No10/2011 standards for food contact with respect to particle migration.
DNase-free	This product is DNase-free. Sensitivity of 10-7 Kunitz units/µL
RNase-free	This product is RNase-free. Sensitivity of 10-9 Kunitz units/µL.
FDA	The plastic film used in the manufacture of LABPLAS sampling bags complies with 21 CFR 177.1520 [(c) 3.2c] of the Food and Drug Administration. Its use is limited to temperatures below 212 F according to Table 2 of 21 CFR 176.170 (c).
FDA	The plastic film used in the manufacture of the LABPLAS sampling bag meets the requirements of 21 CFR 177.1520 of the Food and Drug Administration.
Pyrogens	This product is non-pyrogenic at the endotoxin limit of 2.15 EU/device. Non- pyrogenicity is supported by endotoxin testing of randomly selected samples using the Limulus amebocyte lysate (LAL) gel assay according USP-NF <85> and <161> guidelines.
Sterile	Sterility is provided by dry heat during extrusion of the plastic at temperatures exceeding 428 F. The approach ensures a sterility assurance level (SAL) of 10-3. Continued process effectiveness is demonstrated through periodic sterility testing. Sterility testing follows the USP-NF <71> guideline.

1951, rue Nobel, Sainte-Julie, Québec, Canada, J3E 1Z6

Tél : 1.450.649.7343 | Fax : 1.450.649.3113

labplas@labplas.com | www.labplas.com

